

SERIE 21CD

21CD

AVO - Wheel with conductive polyurethane for industry, diameter 125mm ean 24061

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Heavy duty wheel coated with conductive injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 21CD wheel can be assembled with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793240611

EAN5:24061

Article code:G002100125CCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 280 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	45
Hub width (mm)	49
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	280
Colour	Black
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/