

SERIE 17G-CD

17G-CD

AVO - Wheels with polyurethane conductive for industry, diameter 125mm ean 25148

Material: / **Core:** Conductive polyamide 6 **Scope:** Industry

Description:

Wheel coated with conductive (R 10.000 Ohm) injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer.

Product line: Antistatic/Conductive

EAN13:8018793251488 **EAN5:**25148 **Article code:**12017CD125NRG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 160 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	160
Colour	Grey
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/