

SERIE 21G-CD

21G-CD

AVO - Wheel with conductive polyurethane for industry, diameter 125mm ean 28039

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Heavy duty wheel coated with conductive injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 21G-CD wheel can be assembled with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793280396

EAN5:28039

Article code:G0021CD125GRN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 280 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	45
Hub width (mm)	49
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	280
Colour	Grey
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/