

SERIE 17CD

17CD

AVO - Wheel with conductive polyurethane for industry, diameter 160mm ean 19920

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel coated with conductive injection polyurethane thread 97 Shore A with conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17CD wheel can be combined with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793199209

EAN5:19920

Article code:G2017CD160NBA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 315 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	315
Colour	Black
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/