

SERIE 17G-CD

17G-CD

AVO - Wheel with conductive polyurethane for industry, diameter 200mm ean 28048

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel coated with conductive (R 10.000 Ohm) injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17G-CD wheel can be assembled with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793280488

EAN5:28048

Article code:G2017CD200NBG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 420 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	420
Colour	Grey
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/