

SERIE 17CD

17CD

AVO - Wheel with conductive polyurethane for industry, diameter 60mm ean 21296

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel coated with conductive injection polyurethane thread 97 Shore A with conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17CD wheel can be combined with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793212960

EAN5:21296

Article code:12017CD060NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	60
Band width (mm)	24
Hub width (mm)	10
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	50
Colour	Black
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/