

SERIE 17G-CD

17G-CD

AVO - Wheel with conductive polyurethane for industry, diameter 80mm ean 22763

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel coated with conductive (R 10.000 Ohm) injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17G-CD wheel can be assembled with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793227636

EAN5:22763

Article code:12017CD080NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 80 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	80
Colour	Grey
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/