

SERIE 17G-S

17G-S

AVO - Wheel with thermoplastic polyurethane for industry, diameter 125mm ean 17594

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Product line: Stainless steel, Polyurethane

EAN13: 8018793175944

EAN5: 17594

Article code: G201780125N BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 230 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	230
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/