

SERIE 17

# 17-X

**AVO - Wheel with thermoplastic polyurethane for industry, diameter 175mm ean 23248**

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793232487 **EAN5:**23248 **Article code:**1201700175NCX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 500 DaN

**Rotation:** Stainless steel ball bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	500
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/