

SERIE 21

21

AVO - Wheel with thermoplastic polyurethane for industry, diameter 200mm ean 20377

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13: 8018793203777

EAN5: 20377

Article code: G002100200ORN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 800 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	57
Hub width (mm)	59
Hub version	Roller bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	800
Colour	Ochre
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/