

SERIE 17L

17L

AVO - Wheel with thermoplastic polyurethane for industry, diameter 80mm ean 17393

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13: 8018793173933

EAN5: 17393

Article code: G2017L0080NFA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 125 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	125
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/