

SERIE 17

# 31XB

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 100mm ean 11333

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793113335    **EAN5:**11333    **Article code:**06031XB100NBA



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 150 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle
Brake	/
Plain axle	20X50
Stem type	Plain axle Stem (on request threaded stem)
Finishing	AISI 304 stainless steel