

SERIE 5L

## 5XANT

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 100mm ean 18001

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793180016    **EAN5:**18001    **Article code:**120X50A100NFG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel