

SERIE 17G-S

31XAG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 100mm ean 25343

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel, Polyurethane

EAN13:8018793253437

EAN5:25343

Article code:06831XA100NRG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel