

SERIE 17

31XANTF

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 125mm ean 17200

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake.

Product line: Stainless steel, Polyurethane

EAN13:8018793172004 **EAN5:**17200 **Article code:**06031FA125NBX



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 200 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 125 |
| Band width (mm) | 35 |
| Hub width (mm) | 50 |
| Hub version | Plain bore |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 200 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 42 |
| Ground clearance (mm) | 150 |
| Castor hole (mm) | 12 |
| Static load capacity (DaN) | 250 |
| Structure | Swivel |
| Version | Bolt hole with brake |
| Brake | Front |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |