

SERIE 17

## 31XANTB

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 125mm ean 17259

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793172592 **EAN5:**17259 **Article code:**06031BA125NBX



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 200 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel