

SERIE 17

# 31XANTB

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 125mm ean 17536

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake.

**Product line:** Polyurethane, Stainless steel

**EAN13:**8018793175364    **EAN5:**17536    **Article code:**06031BA125NRX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 200 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Stainless steel roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	AISI 304 stainless steel