

SERIE 61

431XANT

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 125mm ean 25153

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793251532

EAN5:25153

Article code:06431XF12SNRA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Stainless steel roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel