

SERIE 17G-S

## 31XAG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 150mm ean 24978

**Material:** Thermoplastic  
Polyurethane

**Core:**  
Polyamide 6

**Application field:**  
Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, fixed.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793249782

**EAN5:**24978

**Article code:**06831XA150NBG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 200 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 150                        |
| Band width (mm)             | 40                         |
| Hub width (mm)              | 50                         |
| Hub version                 | Plain bore                 |
| Wheel hole (mm)             | 15                         |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 200                        |
| Colour                      | Grey                       |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 80                         |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | 100X085                  |
| Plate hole spacing (mm)    | 080X060                  |
| Plate hole size (mm)       | 8,5X12                   |
| Offset (mm)                | /                        |
| Ground clearance (mm)      | 181                      |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 250                      |
| Structure                  | Fixed                    |
| Version                    | /                        |
| Brake                      | /                        |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |