

SERIE 17G-S

## 31XFG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 160mm ean 27615

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Scope:** Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793276153

**EAN5:**27615

**Article code:**06831FX160NRG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 300 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel