Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

31XANTB

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 200mm ean 17741

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793177412

EAN5:17741

Article code:06031BA201NRX



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing Hardness scale: Shore A Hardness: 97

mic load capacity: 300 DaNConcreteStoneware

ness: 97

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Threaded axle Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel