

SERIE 61

431X

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 200mm ean 25381

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793253819 **EAN5:**25381 **Article code:**06431X0200NRA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|--------------------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 50 |
| Hub width (mm) | 58 |
| Hub version | Stainless steel roller bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 300 |
| Colour | Blue |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 140X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 11X16 |
| Offset (mm) | 55 |
| Ground clearance (mm) | 235 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 380 |
| Structure | Swivel |
| Version | Plate |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |