

SERIE 17G-S

31XANTBG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 200mm ean 27639

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake.

Product line: Stainless steel, Polyurethane

EAN13:8018793276399

EAN5:27639

Article code:06831BX200NRX



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel