

SERIE 61

## 431XF

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 60mm ean 27402

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793274029 **EAN5:**27402 **Article code:**06431FX060NBA



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 60                         |
| Band width (mm)             | 35                         |
| Hub width (mm)              | 50                         |
| Hub version                 | Plain bore                 |
| Wheel hole (mm)             | 12                         |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 70                         |
| Colour                      | Blue                       |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

### Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | /                        |
| Plate hole spacing (mm)    | /                        |
| Plate hole size (mm)       | /                        |
| Offset (mm)                | 42                       |
| Ground clearance (mm)      | 150                      |
| Castor hole (mm)           | 12                       |
| Static load capacity (DaN) | 100                      |
| Structure                  | Swivel                   |
| Version                    | Bolt hole                |
| Brake                      | /                        |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |