

SERIE 17G-S

31XANTFG-S

AVO - Wheel with thermoplastic polyurethane and aisi 304 stainless steel castor for industry, diameter 80mm ean 24128

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake.

Product line: Stainless steel, Polyurethane

EAN13:8018793241281

EAN5:24128

Article code:06831FA080NRG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	12
Static load capacity (DaN)	190
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel