

SERIE 235

## 235BISB

**AVO - Wheel with thermoplastic polyurethane and steel castor for furniture, diameter 40mm ean 19319**

**Material:** Thermoplastic  
Polyurethane

**Core:**  
Polyamide 6

**Application field:**  
Furniture

**Description:**

Wheel with orange Poliurethane flanged with thermoplastic material and castors in zinc-chromium plated pressed steel turning on double rim of balls. Locking device. Recommended use for office furnitures, metal furnishing, electrical household, etc.

**Furniture Castors:**

**Product line:** Furniture

**EAN13:**8018793193191 **EAN5:**19319 **Article code:**SC235BF04001A



## Features

**Minimum temperature:** / **Maximum temperature:** / **Dynamic load capacity:** 15 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 97

## Flooring

- Moquette
- Stoneware

## Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 40                         |
| Band width (mm)             | 18                         |
| Hub width (mm)              | 20                         |
| Hub version                 | Plain bore                 |
| Wheel hole (mm)             | 8                          |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 15                         |
| Colour                      | Red                        |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | 12                         |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

## Support data

|                            |                 |
|----------------------------|-----------------|
| Plate size (mm)            | /               |
| Plate hole spacing (mm)    | /               |
| Plate hole size (mm)       | /               |
| Offset (mm)                | /               |
| Ground clearance (mm)      | 56              |
| Castor hole (mm)           | /               |
| Static load capacity (DaN) | 20              |
| Structure                  | Swivel          |
| Version                    | Axle with brake |
| Brake                      | Front           |
| Plain axle                 | 8X15            |
| Stem type                  | Threaded axle   |
| Finishing                  | Galvanized      |