Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 06445

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

### Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793064453 EAN5:06445 Article code:12031BF100NBA



# **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

 Concrete Stoneware

**Flooring** 

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

## Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	120
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

# Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized