Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

32**B** 

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 06536

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane



**Features** 

Minimum temperature: -20 Maximum temperature: 80

aximum temperature: 80 Dynamic load capacity: 170 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 97

## **Flooring**

- ConcreteStoneware

## Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	1
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized