

SERIE 17

32BISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 10725

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793107259

EAN5:10725

Article code:12032BF100NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

| | |
|------------------------------------|----------------------------|
| Diameter (mm) | 100 |
| Band width (mm) | 30 |
| Hub width (mm) | 30 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 35X11 |
| Dynamic load capacity (DaN) | 170 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|-----------------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 36 |
| Ground clearance (mm) | 131 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 220 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |