

SERIE 5L

5

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 17985

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793179850

EAN5:17985

Article code:1200500100NFG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized