Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17G-S

31ANTG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 22181

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: Stainless steel, Polyurethane



Features

Minimum temperature: -20 Maximum temperature: 80 Dynar

Dynamic load capacity: 120 DaN

ConcreteStoneware

Flooring

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Wheel data

| Diameter (mm) | 100 |
|-----------------------------|----------------------------|
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 1 |
| Dynamic load capacity (DaN) | 120 |
| Colour | Grey |
| Material | Thermoplastic Polyurethane |
| Box pieces | 1 |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| Plate size (mm) | 100X085 |
|----------------------------|------------------|
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 128 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 150 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Front |
| Plain axle | 1 |
| Stem type | 1 |
| Finishing | Galvanized |