

SERIE 17

31ANTF

AVO - Wheels with polyurethane thermoplastic with castor steel for industry, diameter 100mm ean 27200

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Wheel coated with injection Polyurethane 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Polyurethane, Stainless steel

EAN13:8018793272001 **EAN5:**27200 **Article code:**12431FA100NBB



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Red
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized