

SERIE 21-S

60Y-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 100mm ean 27979

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793279796

EAN5:27979

Article code:2106000100BCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11
Offset (mm)	36
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted