

SERIE 17L

31LA

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 06481

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793064811

EAN5:06481

Article code:12031LA125NFA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

- Concrete
- Stoneware

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	125
Band width (mm)	30
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	10
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized