Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17L

# 31LBISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 10675

Material: Thermoplastic

Core: Polyamide 6 Application field:

Polyurethane Polyar

Industry

#### Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793106757

EAN5:10675

Article code:12031LFB125FA



Features Flooring

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

ConcreteStoneware

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

### Wheel data

Diameter (mm)	125
Band width (mm)	30
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	10
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	1
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized