Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17L

31LBIS

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 10680

Material: Thermoplastic Polyurethane

Core:

Application field:

Polyamide 6

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zino-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyurethane

EAN13:8018793106801

EAN5:10680

Article code:12031LF125NCA



Features Flooring

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 150 DaN

ConcreteStoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Wheel data

Diameter (mm)	125
Band width (mm)	30
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	1
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate with brake
Brake	1
Plain axle	1
Stem type	1
Finishing	Galvanized