

SERIE 17

31ANTF

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 11051

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Scope: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793110518

EAN5:11051

Article code:12031FA125NRA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	12
Static load capacity (DaN)	220
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized