

SERIE 17

31A

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 15507

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793155076

EAN5:15507

Article code:12031A012SNCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 130 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	130
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	154
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized