Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

31ANT

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 15516

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: Stainless steel, Polyurethane

EAN13:8018793155168 **EAN5**:15516 **Article code**:120310A12SNCA



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 130 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 97

ConcreteStoneware

Wheel data

| Diameter (mm) | 125 |
|-----------------------------|----------------------------|
| Band width (mm) | 35 |
| Hub width (mm) | 30 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | 35X11 |
| Dynamic load capacity (DaN) | 130 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| Plate size (mm) | 100X085 |
|----------------------------|------------------------|
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 154 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 170 |
| Structure | Swivel |
| Version | Plate Plate with brake |
| Brake | Front |
| Plain axle | 1 |
| Stem type | 1 |
| Finishing | Galvanized |