

SERIE 17

31ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 15522

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793155229 **EAN5:**15522 **Article code:**12031BA12SNCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 130 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	130
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized