

SERIE 21-S

60-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 19545

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793195454

EAN5:19545

Article code:12S6000125BCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 400 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	45
Hub width (mm)	49
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	45
Ground clearance (mm)	166
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized