Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 21-S

## 60BISB-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 27971

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

**EAN13**:8018793279710 **EAN5**:27971 **Article code**:12S60BF125BCN



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 400 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 97

Concrete

Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	45
Hub width (mm)	49
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	161
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized