Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 21-S

60YBISB-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 125mm ean 28000

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793280006

EAN5:28000

Article code:21060BF125BCN



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 400 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 80

Concrete

Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	45
Hub width (mm)	49
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	175
Castor hole (mm)	1
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted