Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

## 31ANT

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 15536

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: Stainless steel, Polyurethane

**EAN13**:8018793155366 **EAN5**:15536 **Article code**:120310A15SNRA



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 130 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 97

ConcreteStoneware

**Flooring** 

## Wheel data

| Diameter (mm)               | 150                        |
|-----------------------------|----------------------------|
| Band width (mm)             | 40                         |
| Hub width (mm)              | 50                         |
| Hub version                 | Roller bearing             |
| Wheel hole (mm)             | 15                         |
| Bearing seat (mm)           | 1                          |
| Dynamic load capacity (DaN) | 130                        |
| Colour                      | Red                        |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | 1                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

## Support data

| Plate size (mm)            | 100X085                |
|----------------------------|------------------------|
| Plate hole spacing (mm)    | 080X060                |
| Plate hole size (mm)       | 8,5X12                 |
| Offset (mm)                | 37                     |
| Ground clearance (mm)      | 179                    |
| Castor hole (mm)           | 1                      |
| Static load capacity (DaN) | 170                    |
| Structure                  | Swivel                 |
| Version                    | Plate Plate with brake |
| Brake                      | Front                  |
| Plain axle                 | 1                      |
| Stem type                  | 1                      |
| Finishing                  | Galvanized             |