Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

31ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 15539

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793155397

EAN5:15539

Article code:12031BA15SNRA



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 130 DaN

Rotation: Roller bearing Hardness scale: Shore A

Hardness: 97

ConcreteStoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	130
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	177
Castor hole (mm)	1
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized