Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17L

31LBISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 20438

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793204385

EAN5:20438

Article code:12031LFB150CA



Features Flooring

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

ConcreteStoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Wheel data

Diameter (mm)	150
Band width (mm)	36
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	1
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle with brake
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized