

SERIE 17L

31LBIS

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 20726

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyurethane

EAN13:8018793207263

EAN5:20726

Article code:12031LF150NC1



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	36
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	37
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized