

SERIE 61

431ANT

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 27228

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793272285

EAN5:27228

Article code:124310A151NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 150 |
| Band width (mm) | 40 |
| Hub width (mm) | 35 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 17 |
| Bearing seat (mm) | 40X12 |
| Dynamic load capacity (DaN) | 200 |
| Colour | Blue |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 140X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 11X16 |
| Offset (mm) | 45 |
| Ground clearance (mm) | 181 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 250 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Front |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |