

SERIE 61

432BISB

AVO - Wheel made of thermoplastic polyurethane with steel castor for industry, diameter 150mm ean 27274

Material: Thermoplastic
Polyurethane

Core: Polyamide
6

Scope:
Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793272742 **EAN5:**27274 **Article code:**12432BF150NCB



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 400 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	400
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	184
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem)
Finishing	Galvanized