

SERIE 61

431F

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 27383

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793273831

EAN5:27383

Article code:12431F015SNCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 130 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	130
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	177
Castor hole (mm)	12
Static load capacity (DaN)	170
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized